



**FR-HT2-411236**

**Dimensions: 41W x 11.6D x 36H**

## Franklin Hutch

1. LPL / PVC Edge: Supplied by Ansonart.
2. Board materials: TITLE VI TSCA certified materials, MDF core density (750kg/m<sup>3</sup> or 46.8lbs/ft<sup>3</sup>)
3. Edge profile: Straight Edge design with PVC edge banding.
4. Light: D-IDL-05-AC100-240V5W.
5. Side panel: LPL over 18mm MDF core with 2mm PVC edge banding.
6. Shelf: LPL over 18mm MDF core with 2mm PVC edge banding.
7. Apron: LPL over 18mm MDF core with wood dowels.
8. Back panel: LPL over 18mm MDF core, 9mm Cork Board with PVC edge banding.
9. Master carton box is 5ply corrugated, bursting test passes 275lbs.
10. Inner packaging: product will be wrapped with PE foam. PE foam will also be used to insert as spacers for doors and drawer fronts and pulls. All corners will have corner-blocking that consist of 3 layers. Outer layer is 3mm hard cardboard. Middle layer is 8mm diameter honeycomb in 20mm thickness. Innermost layer of corner block is 5ply corrugated carton with 7mm thickness. All edges to be protected with an L-shaped block of 13mm diameter honeycomb in 30mm thickness. All face panels to be protected with flat panel 17mm diameter honeycomb. Sizes and thickness of the panels will depend on the requirements for each item.
11. Base frame of MDF/plywood/PB to be placed inside the carton box to increase structural durability for heavier items.
12. Packing method: fully assembled, 1pc per box.